

Signals



Model 4302 LED-Ready Pedestrian Signals

Overview

When you first look at a the Model 4302 pedestrian signal from Peek Traffic, you see a sign of experience — it comes from more than 40 years of building pedestrian signals. Look even closer and you'll find the quality and durability that have made it our most popular signal ever...

Features & Benefits

- Available in polycarbonate and aluminum
- Vandal-resistant construction
- Compatible with our patented clamshell mount, which makes installing the 4302 a quick and clean process
- 4302 Pedestrian Signals are compatible with mounting hardware used on California type A, B, C, and G Pedestrian types
- Z-Crate Visor virtually eliminates sun-phantom
- Designed for long years of service in all types of weather and harsh environmental conditions

Our aluminum and polycarbonate lines are completely interchangeable with one another, allowing you to design the exact pedestrian signal you need. If you need a polycarbonate body with an aluminum door, or an aluminum body with a polycarbonate door, we can accommodate you. Couple that with the ability to exchange the Z-crate for an open visor, or just a door alone, and Peek is sure to have the pedestrian signal that meets your exact needs.



Peek Model 4302 Pedestrian Signals - Available in polycarbonate and aluminum

PEEK signals



Specifications

Property	Description	Environmental	Dustproof and weatherproof when properly mounted
Weight	Aluminum: 15 pounds (6.8kg) Polycarbonate: 12 pounds (5.5kg)	Door Frame Hardware	Stainless steel. Type 304 Stainless steel spring pins. Latching and unlatching of door requires no tools
Dimensions	18.75"H × 9.0"D × 18.5"W (476mm × 229mm × 470mm)	Terminal Strip	An aluminum terminal strip with a pre-mounted three-position quick-connect terminal block is a standard feature in all Model 4302 LED-ready pedestrian signals
Temperature Range	-4°F to +158°F (-20°C to +70°C)		
Z-Crate Visor	100% impregnated black polycarbonate plastic with a flat black finish		
Aluminum Door	One piece corrosion resistant aluminum alloy die-cast door, containing two integrally cast hinge lugs and two latch slots		
"Vision" Z-Crate Visor/Door Combo	One piece door and z-crate combination, cast from 100% impregnated black polycarbonate, including two hinge lugs and two latch slots		
Housing Types	Smooth Top, Shurlock Top, or Ports Cast Closed housings are available in both Aluminum and Polycarbonate. All types contain 72 teeth on each Shurlock (if applicable) to allow for 5° alignment angles and four integrally cast lugs. All housings have a Shurlock boss on the bottom and can be ordered Standard, Drill-Right, Drill Left, or Maintenanced.		
Coatings	All aluminum items are coated with electrostatically applied powder after undergoing a five stage pre-wash. Housings, Open Visors, and Clamshells come in Yellow, Black, or Green, as standard options. Other colors are available upon request. All aluminum doors are powder coated black.		

One Year Limited Warranty

Peek Traffic warrants these products against manufacturing defects in materials and workmanship for one year from the date of shipment from Peek Traffic. Specific contracts and regional laws may vary or alter these terms.



A Signal Group Company

Peek Traffic Corporation

2906 Corporate Way, Palmetto, FL 34221

Phone: (941) 845-1200 • Fax: (941) 365-0837

